

L5 ANSWER 109 OF 575 CA COPYRIGHT 2004 ACS on STN
 AN 133:354110 CA
 ED Entered STN: 07 Dec 2000
 TI Light-weight composite wall **slurry** and method for forming
 composite wall
 IN Tang, Shaolin
 PA Peop. Rep. China
 SO Faming Zhuanli Shenqing Gongkai Shuomingshu, 6 pp.
 CODEN: CNXXEV
 DT Patent
 LA Chinese
 IC ICM C04B028-00
 ICS C04B028-32; C04B018-08; C04B038-00; E04B002-84
 CC 58-3 (Cement, Concrete, and Related Building Materials)
 Section cross-reference(s): 38, 57

FAN.CNT 1

	PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
PI	CN 1251358	A	20000426	CN 1999-114488	19991015
PRAI	CN 1999-114488		19991015		

AB The **slurry** comprises **cement** 60-70, **fly ash** 15-25, thermal-insulating light-wt. aggregate 2-10, air entraining agent 1-5, and additives 2-11 wt.%. Preferably, the **cement** is Cl-O-Mg **cement**, Portland **cement**, or Al sulfate **cement**; the light-wt. aggregate is sawdust, perlite, or crushed foamed particle; the air entraining agent is rosin thermal polymer, ligninsulfonate, or bone glue; the additive is high-efficiency **water** reducer (DNI or JK series products), early strength agent, or waterproofing agent (Ca aluminate or ferrous sulfate). The composite wall is formed by pouring the **slurry** into closed mold through a hole on the top of the mold, curing, removing the mold, and filling the holes with the **slurry**, where steel wires are used to strengthen the wall.

ST composite wall **slurry** light wt; **cement** flyash sawdust
 perlite wall **slurry**; rosin ligninsulfonate bone glue wall
slurry

IT Sawdust
 (aggregate, **slurry** comprising; light-wt. composite wall